




주문생산 볼스크류 : 튜브방식 싱글 NUT C0~C10



플랜지 형식C



플랜지 형식D



(단위 : mm)

형식번호	나사축 외경 d	리드 L	볼크기 Db	곡경 d1	순환수 편X열	기본동 정격하중 C (N)	기본정 정격하중 Co (N)	* 강성 Kns (N/μm)	NUT 치수																	질량	
									외경 D	전장 Lt	와이퍼 종류	플랜지 두께 T	플랜지 외경 D1	플랜지 형식	플랜지 치수						볼트자리						
															X	Y	A	B	G	Q	PCD	M					
																						드릴	캐터바깥	깊이	NUT (kg)	나사축 (kg/100mm)	
GR4010BS-CALR	40	10	6.3500	35.2	1.5×2	34200	89200	320	82	91	L	18	124	C	—	—	—	—	—	Rc1/8	102	11	17.5	10.8	3.40	0.98	
GR4010BS-DALR	40	10	6.3500	35.2	1.5×2	34200	89200	320	82	91	L	18	124	D	—	—	—	—	47	Rc1/8	102	11	17.5	10.8	3.29	0.98	
GR4010DS-CALR	40	10	6.3500	35.2	2.5×1	29300	74300	270	82	71	L	18	124	C	—	—	—	—	—	Rc1/8	102	11	17.5	10.8	2.87	0.98	
GR4010DS-DALR	40	10	6.3500	35.2	2.5×1	29300	74300	270	82	71	L	18	124	D	—	—	—	—	47	Rc1/8	102	11	17.5	10.8	2.75	0.98	
GR4010ES-CALR	40	10	6.3500	35.2	2.5×2	53000	140800	510	82	101	L	18	124	C	—	—	—	—	—	Rc1/8	102	11	17.5	10.8	3.67	0.98	
GR4010ES-DALR	40	10	6.3500	35.2	2.5×2	53000	140800	510	82	101	L	18	124	D	—	—	—	—	47	Rc1/8	102	11	17.5	10.8	3.56	0.98	
GR4012DS-CALR	40	12	7.1438	34.6	2.5×1	35100	79000	290	86	81	L	18	128	C	—	—	—	—	—	Rc1/8	106	11	17.5	10.8	3.46	0.98	
GR4012DS-DALR	40	12	7.1438	34.6	2.5×1	35100	79000	290	86	81	L	18	128	D	—	—	—	—	48	Rc1/8	106	11	17.5	10.8	3.33	0.98	
GR4012ES-CALR	40	12	7.1438	34.6	2.5×2	63700	158000	560	86	117	L	18	128	C	—	—	—	—	—	Rc1/8	106	11	17.5	10.8	4.55	0.98	
GR4012ES-DALR	40	12	7.1438	34.6	2.5×2	63700	158000	560	86	117	L	18	128	D	—	—	—	—	48	Rc1/8	106	11	17.5	10.8	4.42	0.98	
GR4016DS-CAPR	40	16	7.1438	34.6	2.5×1	35100	79000	290	86	91	P	22	128	C	—	—	—	—	—	Rc1/8	106	11	17.5	10.8	3.98	0.98	
GR4016DS-DAPR	40	16	7.1438	34.6	2.5×1	35100	79000	290	86	91	P	22	128	D	—	—	—	—	48	Rc1/8	106	11	17.5	10.8	3.82	0.98	
GR4016GS-CALR	40	16	7.1438	34.6	3.5×1	46800	110600	400	86	107	L	22	128	C	—	—	—	—	—	Rc1/8	106	11	17.5	10.8	4.47	0.98	
GR4016GS-DALR	40	16	7.1438	34.6	3.5×1	46800	110600	400	86	107	L	22	128	D	—	—	—	—	48	Rc1/8	106	11	17.5	10.8	4.31	0.98	
GR4020DS-CAPR	40	20	7.1438	34.6	2.5×1	35100	79000	290	86	105	P	22	128	C	—	—	—	—	—	Rc1/8	106	11	17.5	10.8	4.41	0.98	
GR4020DS-DAPR	40	20	7.1438	34.6	2.5×1	35100	79000	290	86	105	P	22	128	D	—	—	—	—	48	Rc1/8	106	11	17.5	10.8	4.25	0.98	
GR4020GS-CAPR	40	20	7.1438	34.6	3.5×1	46800	110600	400	86	125	P	22	128	C	—	—	—	—	—	Rc1/8	106	11	17.5	10.8	5.02	0.98	
GR4020GS-DAPR	40	20	7.1438	34.6	3.5×1	46800	110600	400	86	125	P	22	128	D	—	—	—	—	48	Rc1/8	106	11	17.5	10.8	4.86	0.98	
GR4032DS-CAPR	40	32	6.3500	35.2	2.5×1	29300	74300	310	78	133	P	22	120	C	—	—	—	—	—	Rc1/8	98	11	17.5	10.8	4.18	0.98	
GR4032DS-DAPR	40	32	6.3500	35.2	2.5×1	29300	74300	310	78	133	P	22	120	D	—	—	—	—	46	Rc1/8	98	11	17.5	10.8	4.05	0.98	
GR4040AS-CAPR	40	40	6.3500	35.2	1.5×1	18800	44600	200	78	114	P	22	120	C	—	—	—	—	—	Rc1/8	98	11	17.5	10.8	3.74	0.98	
GR4040AS-DAPR	40	40	6.3500	35.2	1.5×1	18800	44600	200	78	114	P	22	120	D	—	—	—	—	46	Rc1/8	98	11	17.5	10.8	3.62	0.98	

주) : 표 중 *표의 강성은, 기본동정격하중 (C) 의 30%에 해당하는 축방향하중이 나사축과 강간구에 걸릴때의 탄성변위량으로 부터 강성시험 결과에 근거한 실용치로서 기재되어 있습니다.

· 와이퍼의 종류 : P : 플라스틱 L : 립실